



WIDTH OF EQUIPMENT	HEIGHT OF LEGS
UP TO 24" [UP TP 600mm]	24" [600mm]
24" TO 48" [600mm TO 1.2m]	36" [900mm]
48" AND WIDER [1.2m & WIDER]	48" [1.2m]

NOTES:

THIS DETAIL ALLOWS FOR ROOF SYSTEM MAINTENANCE AROUND THE SUPPORTED EQUIPMENT. THE CONTINUOUS SUPPORT IS PREFERRED IN LIGHTWEIGHT STRUCTURAL SYSTEMS BECAUSE THE EQUIPMENT WEIGHT CAN BE SPREAD ACROSS TWO OR MORE SUPPORTING MEMBERS. WHERE HEAVY STRUCTURAL SYSTEMS ARE USED OR WHERE THE LOAD CAN BE CONCENTRATED OVER A COLUMN, DETAIL SPF-10 MAY BE PREFERRED. A MINIMUM OF 2 FEET [600 mm] OF HORIZONTAL CLEARANCE MUST BE PROVIDED FOR REMOVAL AND REPLACEMENT OF ROOFING AND FLASHING BETWEEN PARALLEL SUPPORTS. REFER TO TABLE ABOVE FOR RECOMMENDATIONS ON VERTICAL CLEARANCE FROM ROOF SURFACE TO BOTTOM OF SUPPORTED EQUIPMENT.

- FLASHING REQUIREMENTS TYPICAL FOR BOTH SIDES OF EQUIPMENT SUPPORT CURB.
- REFER TO THE SHEET METAL SECTION OF THE METAL ROOFING MANUAL FOR JOINERY AND SECUREMENT OPTIONS FOR SHEET METAL.

EQUIPMENT SUPPORT CURB

2001
NOT DRAWN TO SCALE
SPF-9